

View Online at <https://aerobasegroup.com/nsn/5930-01-075-6807>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

1.500 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.875 inches

**Body Diameter:**

0.875 inches

**Bushing Length:**

0.437 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.375 inches

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

F816 a-c-81755

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 tab, solder lug

**Specification Data:**

96906-ms25089 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0