

View Online at <https://aerobasegroup.com/nsn/5930-01-075-6807>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

1.500 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Body Diameter:

0.875 inches

Bushing Length:

0.437 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.375 inches

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F816 a-c-81755

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

96906-ms25089 government standard

Shelf Life:

N/A

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0