## NSN 5930-01-075-8254

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-075-8254

| View Online at https://aerobasegroup.com/nsn/5930-01-075-8254  |
|--|
| Hazardous Locations/environmental Protection:  |
| Dustproof  |
| Body Length:   |
| 0.843 inches   |
| Body Width:  |
| 0.375 inches   |
| Body Height:   |
| 1.625 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.093 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:  |
| 0.500 inches   |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac   |
| End Application:   |
| Runway end indicator lights (reil)   |
| Inclosure Type:  |
| Fully enclosed   |
| Nonpile-up Contact Arrangement:  |
| 3 pole, single throw, normally open, momentary action single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 8.000 amperes resistive ac   |
| Special Features:  |
| W/override and wire harness; function: switch assembly, interlock, 3 pdt-n.O.; reference data: ti 6850.34, fa 9628, 2a3s3, pg 8-13 |
| Terminal Type And Quantity:  |
| 6 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Filg:  |
| A053a0   |
|  |
|  |