

View Online at <https://aerobasegroup.com/nsn/5930-01-075-8608>

**Thread Class:**

2b all threaded hole

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.380 inches

**Overall Height:**

2.437 inches

**Overall Width:**

1.215 inches

**Body Height:**

1.437 inches

**Distance Between Mounting Facility Centers:**

1.250 inches

**Capillary Tube Length:**

30.2 inches

**Bulb Length:**

1.375 inches

**Bulb Diameter:**

0.375 inches

**End Application:**

Air condition 57107

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

250.0 degrees fahrenheit

**Mounting Method:**

Bracket and threaded hole

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.164 inches all threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

96.0 amperes resistive load second voltage and 20.0 amperes inductive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+68.00/+97.00 actuation point degrees fahrenheit and +60.00/+97.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft with scale and external actuation point shaft with scale

**Contact Voltage Rating In Volts:**

240.0 ac at sea level first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0