NSN 5930-01-075-9015

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-075-9015

Hazardous Locations/environmental Protection:
Dustproof and moisture proof
Overall Length:
4.000 inches
Overall Height:
3.216 inches
Overall Width:
1.300 inches
Case Material:
Metal
Actuator Length:
1.570 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
2.125 inches
Housing Length:
4.000 inches
Housing Width:
1.300 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Oe-222/g 34369
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
14
Thread Size:
0.500 inches
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-075-9015 Sensitive Switch - Page 2 of 2



Switch Release Force:
8.0 ounces
Switch Actuating Force:
32.0 ounces
Actuator Movement:
Between 0.219 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Special Features:
Left hand mtg design
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0