

View Online at <https://aerobasegroup.com/nsn/5930-01-075-9015>

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

4.000 inches

Overall Height:

3.216 inches

Overall Width:

1.300 inches

Case Material:

Metal

Actuator Length:

1.570 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.312 inches

Housing Height:

2.125 inches

Housing Length:

4.000 inches

Housing Width:

1.300 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.250 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Oe-222/g 34369

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

14

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

Between 0.219 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Left hand mtg design

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0