## NSN 5930-01-075-9527

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-075-9527

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Width:
0.406 inches
Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
2.932 inches
Actuator Style:
Leaf
Actuator Width:
0.110 inches
Actuator Free Position Height:
0.547 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 grams
Switch Actuating Force:
13.0 grams

**Actuator Movement:** 

Between 0.500 pretravel inches and 0.312 overtravel inches and 0.100 differential inches

## NSN 5930-01-075-9527

Sensitive Switch - Page 2 of 2

**Fiig:** A053a0



Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No