NSN 5930-01-076-4540

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-076-4540

Thread Class: 3a single pressure connection **Thread Length:** 0.550 inches single pressure connection **Overall Length:** 3.000 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit **Mounting Method:** Input port **Features Provided:** Electrical access port Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 7500.00 pounds per square inch gage **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Sensing Element Burst Pressure:** 5500.00 pounds per square inch gage **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 7.0 amperes resistive load second voltage and 4.0 amperes inductive load second voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 250.00 actuation point pounds per square inch gage and 212.50 deactuation point pounds per square inch gage and 37.50 differential point pounds per square inch gage

Pressure Connector Type:

Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage

Flared, threaded external single connection

NSN 5930-01-076-4540

Pressure Switch - Page 2 of 2



Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0