

View Online at <https://aerobasegroup.com/nsn/5930-01-076-5768>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.512 inches

Overall Height:

1.060 inches

Overall Width:

0.421 inches

Bushing Length:

0.290 inches

Body Length:

0.512 inches

Body Width:

0.315 inches

Body Height:

0.360 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Actuator Height:

0.270 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Piga lam30 94756

Mounting Surface To Terminal End Distance:

0.500 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Right angle mtg; unthreaded bushing

Precious Material And Location:

Terminal surfaces gold and contacts silver

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0