

View Online at <https://aerobasegroup.com/nsn/5930-01-076-6446>

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

1.090 inches

Overall Height:

Between 0.515 inches and 0.523 inches

Body Diameter:

0.642 inches

Unthreaded Mounting Hole Diameter:

0.117 inches

Distance Between Mounting Facility Centers:

0.811 inches

End Application:

Svo control cabinet 56232

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.5 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

141.00 actuation point degrees fahrenheit and 157.00 actuation point degrees fahrenheit and 129.00 deactuation point degrees fahrenheit and 139.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0