NSN 5930-01-076-7076

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-076-7076

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.889 inches

Overall Height:

1.031 inches

Overall Width:

1.031 inches

First Flat Length:

0.312 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Clip

Contact Switching Action:

Makes before breaks, breaks before makes single section rear

NSN 5930-01-076-7076

Rotary Switch - Page 2 of 2



| Switch Actuator Positioning Increment: |
|---|
| 30.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 100.0 milliamperes resistive load ac at sea level |
| Precious Material And Location: |
| Clips and rotor blade silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A052b0