NSN 5930-01-076-8191

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Dustproof and corrosion resistant

Body Style:Hole mounted

Overall Length: 2.546 inches



View Online at https://aerobasegroup.com/nsn/5930-01-076-8191

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.125 inches
Overall Width:
0.641 inches
Body Length:
1.812 inches
Body Width:
0.641 inches
Body Height:
1.125 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.145 inches
Actuator Length:
1.812 inches
Actuator Style:
Leaf
Actuator Width:
0.335 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.250 pretravel inches and 0.187 overtravel inches and 0.186 differential inches

NSN 5930-01-076-8191

Sensitive Switch - Page 2 of 2



Contact Loa	d Current Rating	At Maximum	Rated	Voltage:
15.000 ampe	eres resistive ac			

Special Features:

UI approved parts

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0