

View Online at <https://aerobasegroup.com/nsn/5930-01-076-8192>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Overall Length:

0.751 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.537 inches

Overall Width:

0.250 inches

Body Length:

0.751 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.068 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

30.0 dc

End Application:

Helicopter 77272

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 7.5 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.006 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0