NSN 5930-01-077-1992

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-077-1992

Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Dustproof						
Center To Center Distance Between Mounting Facilities Parallel To Length:						
0.375 inches						
Body Length:						
0.781 inches						
Body Width:						
0.250 inches						
Body Height:						
0.500 inches						
Unthreaded Mounting Hole Diameter:						
0.088 inches						
Actuator Length:						
0.875 inches						
Actuator Style:						
Roller arm						
Actuator Free Position Height:						
0.375 inches						
Actuator Roller Diameter:						
0.188 inches						
Actuator Roller Width:						
0.125 inches						
Maximum Voltage Rating In Volts:						
125.0 ac						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Panel						
Nonpile-up Contact Arrangement:						
1 pole, double throw, one position momentary single switch unit						
Switch Release Force:						
10.0 grams						
Switch Actuating Force:						
26.0 grams						
Actuator Movement:						
0.406 pretravel inches and 0.062 overtravel inches and 0.050 differential inches						
Contact Load Current Rating At Maximum Rated Voltage:						
100.000 milliamperes resistive ac						

3 tab, solder lug

Terminal Type And Quantity:

NSN 5930-01-077-1992

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0