

View Online at <https://aerobasegroup.com/nsn/5930-01-077-9806>

Overall Length:

4.375 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

2.094 inches

Overall Width:

4.000 inches

Mounting Slot Width:

Between 0.188 inches and 0.198 inches

Body Length:

2.625 inches

Body Width:

3.625 inches

Distance Between Mounting Facility Centers:

3.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and slot

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.5 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+100.00 actuation point pounds per square inch gage and +0.00/+100.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0