## NSN 5930-01-077-9806

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-077-9806

Overall Length:
4.375 inches
Outside Diameter:
0.250 inches single connection
Overall Height:
2.094 inches
Overall Width:
4.000 inches
Mounting Slot Width:
Between 0.188 inches and 0.198 inches
Body Length:
2.625 inches
Body Width:
3.625 inches
Distance Between Mounting Facility Centers:
3.625 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and slot
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
6.5 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.00/+100.00 actuation point pounds per square inch gage and +0.00/+100.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
External deactuation point knob and external actuation point knob
Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

## NSN 5930-01-077-9806

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Ptf-sae short single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0