## NSN 5930-01-078-1319

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-078-1319

**Thread Class:** 

3b all pressure connection

**Thread Length:** 

0.709 inches all pressure connection

**Hazardous Locations/environmental Protection:** 

Dustproof and explosion proof

**Overall Length:** 

Between 2.500 inches and 3.270 inches

**Overall Height:** 

3.910 inches

**Overall Width:** 

2.400 inches

**Body Length:** 

Between 2.500 inches and 3.270 inches

**Pressure Switch Type:** 

Differential

**Operating Tempurature Rating:** 

Between 32.0 degrees fahrenheit and 185.0 degrees fahrenheit

**Mounting Method:** 

Inlet connection and outlet connection

**Features Provided:** 

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 all pressure connection

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

150.00 pounds per square inch gage

**Thread Size:** 

0.562 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:** 

300.00 pounds per square inch gage

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

3.0 amperes inductive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:** 

0.60 actuation point gallons per minute and 0.40 deactuation point gallons per minute and 0.20 differential point gallons per minute

# NSN 5930-01-078-1319

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:	Contact	Voltage	Rating	In	Volts
----------------------------------	---------	---------	--------	----	-------

28.0 dc at sea level single voltage

### **Pressure Connector Type:**

Plain, threaded internal all connections

#### **Test Data Document:**

81349-mil-s-28788 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unf all pressure connection

#### **Specification Data:**

81349-mil-s-28788/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0