

View Online at <https://aerobasegroup.com/nsn/5930-01-078-3521>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 3.400 inches and 3.500 inches

**Overall Height:**

Between 0.992 inches and 1.008 inches

**Overall Width:**

Between 0.742 inches and 0.758 inches

**Body Length:**

Between 2.075 inches and 2.175 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.178 inches and 0.182 inches

**Distance Between Mounting Facility Centers:**

Between 1.420 inches and 1.460 inches

**End Application:**

An/bqq-5 52088

**Operating Temperature Rating:**

85.0 degrees celsius and 0.0 degrees celsius

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Decrease

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

100.00 actuation point feet per minute and 800.00 deactuation point feet per minute and 1800.00 deactuation point feet per minute

**Contact Voltage Rating In Volts:**

29.0 dc at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0