

View Online at <https://aerobasegroup.com/nsn/5930-01-078-3521>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 3.400 inches and 3.500 inches

Overall Height:

Between 0.992 inches and 1.008 inches

Overall Width:

Between 0.742 inches and 0.758 inches

Body Length:

Between 2.075 inches and 2.175 inches

Unthreaded Mounting Hole Diameter:

Between 0.178 inches and 0.182 inches

Distance Between Mounting Facility Centers:

Between 1.420 inches and 1.460 inches

End Application:

An/bqq-5 52088

Operating Temperature Rating:

85.0 degrees celsius and 0.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

100.00 actuation point feet per minute and 800.00 deactuation point feet per minute and 1800.00 deactuation point feet per minute

Contact Voltage Rating In Volts:

29.0 dc at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0