NSN 5930-01-078-3523

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-076-3523
Thread Class:
2b 1st mounting facility
Overall Length:
5.594 inches
Overall Height:
4.219 inches
Overall Width:
4.375 inches
Unthreaded Mounting Hole Diameter:
0.312 inches 2nd mounting facility
Distance Between Mounting Facility Centers:
3.812 inches 2nd mounting facility
Individual Section Quantity:
6
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
2 each section periphery
Mounting Facility Circle Radius:
1.609 inches 1st mounting facility
Mounting Method:
Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility
Features Provided:
Actuator knob and dummy section
Thready Qty Per Inch (tpi):
20 1st mounting facility
Thread Size:
0.250 inches 1st mounting facility
Contact Voltage Rating In Volts:
440.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Two position in-line 2nd mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Breaks before makes each section periphery

NSN 5930-01-078-3523

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0