NSN 5930-01-078-4294

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-078-4294

Thread Class:
2a single pressure connection
Thread Length:
0.562 inches single pressure connection
Outside Diameter:
0.438 inches single connection
Pressure Switch Type:
Gage
Mounting Method:
Line
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
7500.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
1 pole, double throw, one position momentary Terminal Type:
Terminal Type:
Terminal Type: Connector, receptacle
Terminal Type: Connector, receptacle Contact Load Current Rating:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type: Flared, threaded external single connection
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type: Flared, threaded external single connection Frequency In Hertz:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type: Flared, threaded external single connection Frequency In Hertz: 60.0 second voltage
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type: Flared, threaded external single connection Frequency In Hertz: 60.0 second voltage Thread Series Designator:
Terminal Type: Connector, receptacle Contact Load Current Rating: 7.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 75.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level third voltage Pressure Connector Type: Flared, threaded external single connection Frequency In Hertz: 60.0 second voltage Thread Series Designator: Uns single pressure connection

--

NSN 5930-01-078-4294

Pressure Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0