NSN 5930-01-078-6484

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-078-6484

## **Thread Length:**

0.375 inches single mounting facility

#### **Overall Length:**

4.740 inches

# First Flat Length:

0.250 inches single actuator

## Flat Height:

0.210 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

4.740 inches single actuator

#### Individual Section Quantity:

2

#### Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

15 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.468 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

15 single actuator

#### Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

20.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-01-078-6484

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0