

View Online at <https://aerobasegroup.com/nsn/5930-01-078-6485>

Thread Length:

0.470 inches single mounting facility

Overall Length:

4.900 inches

First Flat Length:

0.690 inches single actuator

Flat Height:

0.187 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

3.000 inches single actuator

Overall Diameter:

2.120 inches

Nonturn Device Radius:

0.372 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.468 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0