

View Online at <https://aerobasegroup.com/nsn/5930-01-078-6742>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.849 inches

Overall Height:

0.300 inches

Body Diameter:

0.660 centimeters

Mounting Slot Width:

Between 0.104 inches and 0.109 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

End Application:

6780-01-072-5956 embedded digital data interface input output device

Temperature Sensing Element Type:

Disc

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

18.00 actuation point degrees fahrenheit and 26.00 actuation point degrees fahrenheit and 13.00 deactuation point degrees fahrenheit and 21.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Disc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0