NSN 5930-01-078-6747

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-078-6747

| Overall Length: |
|---|
| 3.688 inches |
| Overall Height: |
| 3.688 inches |
| First Flat Length: |
| 0.875 inches single actuator |
| Shaft Diameter: |
| 0.375 inches single actuator |
| Shaft Length: |
| 1.188 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.640 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Specificationial Markings: |
| Arrow sign |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.280 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.280 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section front |
| Throw Quantity: |
| 1 single section rear |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 500.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Terminal Type: |
| — • • |

Tab w/screw

NSN 5930-01-078-6747

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes single section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Contact Load Current Rating:** 30.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0