

View Online at <https://aerobasegroup.com/nsn/5930-01-078-7261>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.750 inches

Body Diameter:

1.440 inches

Overall Diameter:

1.870 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Clamp and input port

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1.00 actuation point pounds per square inch and 0.25 deactuation point pounds per square inch and 0.75 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0