

View Online at <https://aerobasegroup.com/nsn/5930-01-078-7269>

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

Between 0.385 inches and 0.415 inches

Body Height:

Between 0.610 inches and 0.640 inches

Unthreaded Mounting Hole Diameter:

Between 0.124 inches and 0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Length:

0.970 inches

Actuator Style:

Leaf

Actuator Width:

Between 0.155 inches and 0.185 inches

Actuator Free Position Height:

Between 0.131 inches and 0.257 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 grams

Switch Actuating Force:

35.0 grams

Actuator Movement:

Between 0.110 pretravel inches and 0.090 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0