

View Online at <https://aerobasegroup.com/nsn/5930-01-078-7950>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.430 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.770 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.207 inches single actuator and 0.213 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

0.370 inches single actuator

**Overall Diameter:**

1.100 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 10: 30 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

10 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level 2.0 amperes inductive load dc at sea level and 3.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0