NSN 5930-01-079-1775

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-079-1775

Overall Length:					
14.188 inches					
Power Cable Length:					
Between 24.000 inches and 26.000 inches					
Ac Voltage Rating:					
30.0 volts					
Dc Voltage Rating:					
40.0 volts					
Frequency Rating:					
60.0 hertz					
Overall Diameter:					
Any acceptable					
Actuation Method:					
Buoyancy					
Electrical Connection Type:					
Cable					
Internal Battery Accommodation:					
Not included					
Current Rating At Maximum Rated Voltage:					
0.08 amperes resistive load					
Voltage Rating At Maximum Rated Current:					
120.0 volts					
Float Quantity:					
1					
Operating Tempurature Rating:					
Between 0.0 degrees fahrenheit and 300.0 degrees fahrenheit					
Mounting Method:					
Flange					
Mounting Position:					
Vertical					
Maximum Current Rating:					
0.17 amperes resistive load					
Contact Arrangement:					
Single-pole, double throw, normally open					
Relay:					
Not included					
Liquid Type For Which Designed:					
Various fuels					
Float Effective Travel:					
Any acceptable					
Tank Insertion Length:					
. a.m. moor don Eongan					

Between 11.938 inches and 12.062 inches

NSN 5930-01-079-1775

Liquid Level Switch - Page 2 of 2



P	h	2	s	Δ	•

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T109-d