NSN 5930-01-079-2532

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Weatherproof



View Online at https://aerobasegroup.com/nsn/5930-01-079-2532

(Overall Length:
(0.750 inches
(Center To Center Distance Between Mounting Facilities Parallel To Length:
(0.250 inches
(Overall Height:
(0.676 inches
(Overall Width:
(0.345 inches
ı	Body Length:
(0.750 inches
ı	Body Width:
(0.345 inches
ı	Body Height:
(0.516 inches
(Case Material:
F	Plastic
ı	Inthreaded Mounting Hole Diameter:
(0.089 inches
,	Actuator Style:
F	Round
,	Actuator Free Position Height:
(0.420 inches
ı	Maximum Voltage Rating In Volts:
•	15.0 ac and 28.0 dc
ı	End Application:
F	Frm86 77777
ı	nclosure Type:
ŀ	Hermetically sealed
ı	Mounting Method:
Į	Jnthreaded hole
ı	Nonpile-up Contact Arrangement:
•	pole, double throw, one position momentary single switch unit
;	Switch Release Force:
6	5.0 ounces
\$	Switch Actuating Force:
E	Between 16.0 ounces and 22.0 ounces
(Contact Load Current Rating At Maximum Rated Voltage:
Ę	5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

NSN 5930-01-079-2532

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0