

View Online at <https://aerobasegroup.com/nsn/5930-01-079-6075>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.876 inches

Body Width:

0.346 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Free Position Height:

0.475 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Two 20 awg. 24.000 in. Wire leads marked circuit identification and wire gage at 2.000 in. Intervals, common 20, normally closed 20

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0