

View Online at <https://aerobasegroup.com/nsn/5930-01-079-7406>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.688 inches

**Overall Height:**

8.438 inches

**Overall Width:**

5.125 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.875 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**End Application:**

Jet engine t standard 54932

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and threaded stud

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

28 all threaded stud

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

225.00 pounds per square inch

**Thread Size:**

0.250 inches all threaded stud

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.25/+1.00 actuation point pounds per square inch and +0.25/+1.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

1.00 actuation point pounds per square inch and 0.00 differential point pounds per square inch and 100.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Thread Series Designator:**

Unf all threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0