

View Online at <https://aerobasegroup.com/nsn/5930-01-079-7406>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.688 inches

Overall Height:

8.438 inches

Overall Width:

5.125 inches

Longest Horizontal Distance Between Mounting Centers:

4.875 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

End Application:

Jet engine t standard 54932

Pressure Switch Type:

Differential

Mounting Method:

Bracket and threaded stud

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

28 all threaded stud

Contact Action Stimulus:

Increase

Proof Pressure:

225.00 pounds per square inch

Thread Size:

0.250 inches all threaded stud

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.25/+1.00 actuation point pounds per square inch and +0.25/+1.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

1.00 actuation point pounds per square inch and 0.00 differential point pounds per square inch and 100.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0