

View Online at <https://aerobasegroup.com/nsn/5930-01-079-7407>

Overall Length:

16.120 inches

Overall Height:

4.400 inches

Overall Width:

2.150 inches

Body Length:

1.810 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

Between 3.940 inches and 4.060 inches

Capillary Tube Length:

12.5 inches

Bulb Length:

4.870 inches

Bulb Diameter:

1.250 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between 30.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

22.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+30.00/+110.00 actuation point degrees fahrenheit and +30.00/+110.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob with scale and external deactuation point knob with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0