

View Online at <https://aerobasegroup.com/nsn/5930-01-079-7421>

Body Style:

Bushing mount

Overall Length:

0.510 inches

Overall Height:

1.502 inches

Overall Width:

0.450 inches

Bushing Length:

0.312 inches

Body Length:

0.510 inches

Body Width:

0.450 inches

Body Height:

0.470 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

0.610 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

A-4m aircraft

Mounting Surface To Terminal End Distance:

0.580 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

Fine diamond knurl 0.200 in. Lg on actuator

Precious Material And Location:

Contacts and terminal surfaces silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0