NSN 5930-01-079-7425

Sensitive Switch - Page 1 of 2

4.0 grams



View Online at https://aerobasegroup.com/nsn/5930-01-079-7425

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.937 inches
Overall Height:
0.875 inches
Overall Width:
0.750 inches
Body Length:
1.219 inches
Body Width:
0.531 inches
Body Height:
0.688 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter: 0.122 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.343 inches
Actuator Length:
0.100 inches
Actuator Style: Leaf
Actuator Adapter Style: Wire
Maximum Voltage Rating In Volts:
125.0 ac
End Application:
Shipboard rea 91417
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 grams
Switch Actuating Force:

NSN 5930-01-079-7425

Sensitive Switch - Page 2 of 2



Δ	cti	iatoi	r M	OV	em	ent	
~	LLU	aw	IVI	UV		en	

Between 21.0 pretravel degrees and 15.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive ac

Precious Material And Location:

Contacts gold and terminal surfaces silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0