NSN 5930-01-079-7426

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-079-7426

| Body Style: |
|--|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Weatherproof |
| Overall Length: |
| 0.876 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.375 inches |
| Overall Height: |
| 18.695 inches |
| Overall Width: |
| 0.346 inches |
| Body Length: |
| 0.876 inches |
| Body Width: |
| 0.346 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.087 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.094 inches |
| Actuator Free Position Height: |
| 0.425 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| End Application: |
| Adapter assembly 73342 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 5.0 ounces and 17.0 ounces |

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

NSN 5930-01-079-7426

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Eighteen foot leads

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0