## NSN 5930-01-079-7426

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-079-7426

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
0.876 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
18.695 inches
Overall Width:
0.346 inches
Body Length:
0.876 inches
Body Width:
0.346 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.087 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Free Position Height:
0.425 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
Adapter assembly 73342
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

## NSN 5930-01-079-7426

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:** 

Eighteen foot leads

**Terminal Type And Quantity:** 

2 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0