NSN 5930-01-079-8509

Hazardous Locations/environmental Protection:

Pressure Switch - Page 1 of 2

General purpose-nema type 1

Contact Stimulus Rating:

square inch

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-079-8509

3.188 inches
Overall Height:
4.906 inches
Overall Width:
1.562 inches
Body Height:
2.750 inches
End Application:
Jet engine t standard 54932
Pressure Switch Type:
Gage
Mounting Method:
Bracket and threaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
75.00 pounds per square inch
Thread Size:
0.190 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+1.50/+52.50 actuation point pounds per square inch and +0.00/+50.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal deactuation point hex nut and internal actuation point hex nut

20.00 actuation point pounds per square inch and 1.50 differential point pounds per square inch and 2.50 differential point pounds per

NSN 5930-01-079-8509

Pressure Switch - Page 2 of 2



Contact	Voltage	Rating	ln	Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0