NSN 5930-01-079-9021

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-079-9021

| Body Style: |
|--|
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 3.500 inches |
| Overall Width: |
| 1.500 inches |
| Body Diameter: |
| 1.500 inches |
| Bushing Length: |
| 1.000 inches |
| Body Length: |
| 2.100 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.370 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double make, two positions momentary single switch unit |
| Switch Release Force: |
| 80.0 ounces |
| Switch Actuating Force: |
| 144.0 ounces |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes inductive dc |

Special Features: Leads 240.000 in. Lg

NSN 5930-01-079-9021 Sensitive Switch - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Unef |
| Terminal Type And Quantity: |
| 4 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0