## NSN 5930-01-079-9022

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-079-9022

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof  Overall Length:
Overall Length:
2.125 inches  Contar To Contar Dictarea Between Mounting Facilities Berellel To Length:
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Height: 0.850 inches
Overall Width:
0.400 inches
Body Length:
1.090 inches
Body Width:
0.400 inches
Body Height:
0.620 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Style:
Leaf
Actuator Width:
0.154 inches
Actuator Free Position Height:
0.600 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 grams
Switch Actuating Force:

20.0 grams

## NSN 5930-01-079-9022

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

0.281 pretravel inches and 0.160 overtravel inches and 0.070 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

-----

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A053a0