

View Online at <https://aerobasegroup.com/nsn/5930-01-079-9608>

Thread Class:

3a single pressure connection

Thread Length:

0.758 inches single pressure connection

Overall Length:

2.935 inches

Outside Diameter:

0.875 inches single connection

Overall Height:

2.750 inches

Body Diameter:

2.370 inches

Body Height:

1.492 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Inlet connection and terminal

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch gage

Thread Size:

0.875 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

50.0 milliamperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+20.00/+150.00 actuation point pounds per square inch gage and +20.00/+150.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

0.40 actuation point gallons per minute and 0.30 deactuation point gallons per minute

Contact Voltage Rating In Volts:

50.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0