

View Online at <https://aerobasegroup.com/nsn/5930-01-080-0434>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Flame resistant

**Overall Length:**

1.046 inches

**Overall Height:**

0.343 inches

**Overall Width:**

0.343 inches

**Body Diameter:**

0.343 inches

**Bushing Length:**

0.282 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.156 inches

**Actuator Height:**

0.136 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-s-8805/96 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0