Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-080-4407

### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

2.430 inches

### **Overall Height:**

1.825 inches

#### **Overall Width:**

1.750 inches

### Individual Section Quantity:

# 3

### Longest Horizontal Distance Between Mounting Centers:

2.094 inches single mounting facility

### Longest Vertical Distance Between Mounting Centers:

## 0.900 inches single mounting facility

### **End Application:**

Sonar, an/bqq-5 & 6, ship, ohio class ssn (trident), sturgeon class ssn (637), sonar, an/bsy- (v), submarine acoustic sonar systems.

#### Mounting Method:

Threaded hole single mounting facility

### Actuator Type:

Thumbwheel all actuators

## Features Provided:

Rfi shielding

### Thready Qty Per Inch (tpi):

56 1st mounting facility

#### Thread Size:

0.086 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### **Mounting Facility Pattern:**

Four position rectangular single mounting facility

## Switch Actuator Indexing Position Quantity:

10 all actuators

### **Criticality Code Justification:**

Feat

#### Terminal Type:

Printed circuit

#### **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

#### **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Code Indicating Wheel Switch - Page 2 of 2



Contact Arrangement Truth Table: Bcd complement only, 1 pole - 10 positions each section

## **Special Features:**

Lamp bus bar bonded to housing. Weapon system essential.

Color:

White each indicator marking

Precious Material And Location:

Contact surfaces gold

## **Precious Material:**

Gold

Style Designator:

Rectangular inline indicating

### **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A052b0