

View Online at <https://aerobasegroup.com/nsn/5930-01-080-4407>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.430 inches

Overall Height:

1.825 inches

Overall Width:

1.750 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.094 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

End Application:

Sonar, an/bqq-5 & 6, ship, ohio class ssn (trident), sturgeon class ssn (637), sonar, an/bsy- (v) , submarine acoustic sonar systems.

Mounting Method:

Threaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

56 1st mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Criticality Code Justification:

Feat

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Contact Arrangement Truth Table:

Bcd complement only, 1 pole - 10 positions each section

Special Features:

Lamp bus bar bonded to housing. Weapon system essential.

Color:

White each indicator marking

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0