NSN 5930-01-080-5779

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-080-5779

Overall Length:						
2.750 inches						
Overall Height:						
1.875 inches						
Overall Width:						
1.875 inches						
First Flat Length:						
0.625 inches single actuator						
Flat Height:						
0.250 inches single actuator						
Shaft Diameter:						
0.312 inches single actuator						
Shaft Length:						
0.750 inches single actuator						
Unthreaded Mounting Hole Diameter:						
0.156 inches single mounting facility						
Individual Section Quantity:						
2						
Longest Horizontal Distance Between Mounting Centers:						
1.437 inches single mounting facility						
Longest Vertical Distance Between Mounting Centers:						
1.437 inches single mounting facility						
Switch Contact Basic Design:						
Nonpile-up symmetrical						
Pole Quantity:						
1 each section rear						
Throw Quantity:						
3 each section rear						
Mounting Method:						
Unthreaded hole single mounting facility						
Features Provided:						
Actuator knob						
Contact Voltage Rating In Volts:						
600.0 ac at sea level						
Mounting Facility Pattern:						
Four position rectangular single mounting facility						
Switch Actuator Indexing Position Quantity:						
4 single actuator						
Shaft Type:						
Round, flatted, threaded hole single actuator						
Terminal Type:						
Correction						

Screw

NSN 5930-01-080-5779

Rotary Switch - Page 2 of 2



Cc	nta	ct S	witcl	hina	Actic	'n.
v	nıta	UL O	WILL	ши	Actic	""

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

16.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0