## NSN 5930-01-080-6350

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-080-6350

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
3.660 inches
Overall Width:
3.440 inches
Case Material:
Metal
Actuator Length:
3.140 inches
Actuator Style:
Leaf
Actuator Adapter Style:
Nonadjustable arm
Housing Height:
2.572 inches
Housing Length:
3.660 inches
Housing Width:
2.015 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.812 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.750 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
14
Thread Size:
0.500 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
48.0 ounces

Between 0.156 pretravel inches and 0.141 overtravel inches and 0.060 differential inches

## NSN 5930-01-080-6350

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

6 screw

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0