

View Online at <https://aerobasegroup.com/nsn/5930-01-081-0013>

Body Style:

Hole mounted

Overall Length:

0.525 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.281 inches

Overall Height:

0.810 inches

Body Length:

0.510 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.353 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.630 inches

Actuator Roller Diameter:

0.187 inches

Actuator Roller Width:

0.125 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

1.5 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.035 pretravel inches and 0.006 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes motor dc and 7.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0