

View Online at <https://aerobasegroup.com/nsn/5930-01-081-3787>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

0.750 inches

Overall Height:

3.070 inches

Overall Width:

0.750 inches

Body Length:

0.679 inches

Body Width:

0.750 inches

Body Height:

2.950 inches

Case Material:

Plastic

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Amber single actuator and green single actuator

Actuator Inscription:

Power on single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Anusm 435 15942

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Unit has conductive finish; five terminals for lamps

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

17 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0