

View Online at <https://aerobasegroup.com/nsn/5930-01-081-4761>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

0.685 inches

**Overall Height:**

2.600 inches

**Overall Width:**

0.685 inches

**Body Length:**

0.685 inches

**Body Width:**

0.685 inches

**Body Height:**

1.145 inches

**Case Material:**

Plastic

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 20.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

**Special Features:**

Keying angle 300 degrees cw rotation of master tab from point zero

**Precious Material And Location:**

Terminal surfaces gold

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0